

you can  
**Canon**

## EOS 300D DIGITAL

*Professional digital photography.  
No longer just for the professionals.*



OFFICIAL PARTNER

It's the affordable digital SLR that everyone has been waiting for. The EOS 300D has a 6.3 megapixel CMOS sensor, for high image definition, plus the feature set and vast range of accessories and lenses that is synonymous with the EOS name. It's a camera that extends the creative possibilities of beginners and experienced users alike.

## EOS 300D FEATURES

- 6.3 megapixel Canon CMOS sensor
- 7-point wide-area AF
- 2.5 frames per second continuous shooting
- High performance DIGIC processor
- 100 – 1600 ISO speed range
- Colour Space selection, including Adobe RGB
- Simultaneous RAW and JPEG shooting
- Simple, easy-to-use operations
- Compatible with entire range of Canon EF lenses and EX Speedlites
- Available as body only or body plus exclusively designed compact EF-S (18-55mm) lens kit
- PictBridge, Canon Direct Print and Bubble Jet Direct compatible – no PC required
- Full suite of imaging software, including Adobe Photoshop Elements
- Compact and lightweight body weighing just 560g

## EOS 300D SPECIFICATIONS

<b>IMAGE SENSOR</b>	Type Effective Pixels Total Pixels Aspect Ratio Low-Pass Filter Colour Filter Type	22.7 x 15.1mm CMOS Approx. 6.3M Approx. 6.5M 3:2 Built-in/Fixed Primary Colour	<b>VIEWFINDER (CONT.)</b>	Focusing Screen Mirror  Viewfinder Information	Fixed Quick-return half mirror (Transmission: reflection ratio of 40:60) AF Points, AE/FE lock, AEB, Shutter speed, aperture, exposure level/compensation, Max. burst, AF/MF focus confirmation, CF warning Provided	<b>OTHER FEATURES (CONT.)</b>	Playback zoom Display Formats	2x-10x (1) Single image with information* (2) Single image* (3) Auto play (4) 9 image index (5) Magnified view (P.Fn-30)
<b>IMAGE PROCESSOR</b>	Type	DIGIC	<b>DEPTH OF FIELD PREVIEW</b>	Depth of field preview	Provided	<b>IMAGE ERASE PROTECTION</b>	Image Erase Self Timer Menu Categories	1 image 1 image/all images/initialize 10 sec. (1) Shooting Menus: 7 (2) Playback Menus: 6 (3) Setup menus: 13 (6+7) English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Chinese, Japanese Update possible by the user
<b>LENS</b>	Lens Mount Focal Length	EF/EF-S 1.6x Multiplication with EF/EF-S lens fitted	<b>LCD MONITOR</b>	Monitor Coverage Brightness	1.8", TFT (approx. 118,000 pixel) Approx. 100% (for JPEG images) Adjustable to one of five levels	<b>MENU LANGUAGES</b>	Menu Languages	Firmware Update
<b>FOCUSING</b>	Type AF System/Points AF working range AF Modes	TTL-CT-SiR with a CMOS sensor 7-point AF EV 0.5-18 (at 20°C & ISO 100) AI FOCUS ONE SHOT AI SERVO	<b>FLASH</b>	Modes HotShoe/PC terminal X-sync Red-eye Reduction Flash Exposure Compensation Flash Exposure Bracketing Flash Exposure Lock Second Curtain Synchronisation Built-in Flash Range	Auto, Manual Flash On/Off, Red-Eye Reduction Yes/ 1/200th sec. Yes No Yes No Coverage up to 18mm focal length (28mm equivalent)	<b>FIRMWARE UPDATE</b>	Computer Other	<b>INTERFACE</b>
AF Point Selection Selected AF point display	Predictive AF AF Lock AF Assist Beam Manual Focus	Automatic selection, Manual selection Superimposed in viewfinder and indicated on rear LCD panel Yes Yes Yes Selected on lens	<b>SHOOTING</b>	Modes Continuous Shooting Recording Pixels / Compression Image Size	Auto, Portrait, Landscape, Close-up, Sports, Night portrait, Flash off, P, Tv, Av, M, A-Dep 2.5 fps (speed maintained for up to 4 images)	<b>POWER SOURCE</b>	Batteries Battery life	USB (PTP) Video output (PAL/NTSC)
<b>EXPOSURE CONTROL</b>	Metering modes  Metering Range AE Lock	TTL full aperture metering with 35-zone SPC, 35-Point Evaluative, Partial (approx. 9% of viewfinder), Centre-weighted EV 1-20 (at 20°C with 50mm f/1.4 lens ISO 100) Auto: Operates in 1-shot AF mode with evaluative metering when focus is achieved Manual: Works independently at all times, and in creative zone modes.	<b>COMPRESSION</b>	Compression File Format Still Image Format	Auto, Portrait, Landscape, Close-up, Sports, Night portrait, Flash off, P, Tv, Av, M, A-Dep 2.5 fps (speed maintained for up to 4 images)	<b>BATTERY CHECK</b>	Battery check Power saving A/C Power Supply	<b>MEMORY CARD</b>
Exposure Compensation AEB ISO Speed Equivalent	<b>SHUTTER</b>	+/- 2 EV, 1/3-stop increments +/- 2 EV, 1/3-stop increments AUTO (100, 200, 400), 100, 200, 400, 800, 1600	<b>RAW+JPEG simultaneous recording</b>	RAW+JPEG simultaneous recording File Numbering	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, RAW & JPEG simultaneous recording, Digital Print Order Format (DPOF) Version 1.1 compliant Provided (1) Consecutive numbering (2) Auto reset (3) Manual reset 2 Standard Parameters plus up to three custom processing parameters can be set.	<b>ACCESSORIES</b>	Case Lenses Flash  Battery Grip Remote Controller/Switch Power Supply & Battery Chargers	CompactFlash Type I/II (Microdrive compatible)
<b>SHUTTER</b>	Type Speed Shutter release	Electronically-controlled focal-plane shutter 30 - 1/4000 sec., Bulb. Soft touch electromagnetic release	<b>PROCESSING PARAMETERS</b>	Processing Parameters	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, RAW & JPEG simultaneous recording, Digital Print Order Format (DPOF) Version 1.1 compliant Provided (1) Consecutive numbering (2) Auto reset (3) Manual reset 2 Standard Parameters plus up to three custom processing parameters can be set.	<b>PC</b>	ZoomBrowser EX (PhotoRecord)/ImageBrowser PhotoStitch, RemoteCapture, File Viewer Utility TWAIN (Windows 98/2000), WIA (Windows Me) Photoshop Elements v2	<b>SUPPORTED OPERATING SYSTEM</b>
<b>WHITE BALANCE</b>	Type Settings	Auto white balance with the imaging sensor AWB, Daylight, Shade, Cloudy, Tungsten, Fluorescent, Flash, Custom +/-3 stops in full stop increments	<b>DIRECT PRINT</b>	Canon Printers	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, RAW & JPEG simultaneous recording, Digital Print Order Format (DPOF) Version 1.1 compliant Provided (1) Consecutive numbering (2) Auto reset (3) Manual reset 2 Standard Parameters plus up to three custom processing parameters can be set.	<b>SOFTWARE</b>	Browsing & Printing Other Drivers Image Manipulation	Windows 98 (including SE)/2000/Me/XP OS 9.0 - 9.2, OS X v10.1/v10.2
<b>WB BRACKETING</b>	WB Bracketing	+/-3 stops in full stop increments	<b>RAW+JPEG simultaneous recording</b>	RAW+JPEG simultaneous recording File Numbering	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, RAW & JPEG simultaneous recording, Digital Print Order Format (DPOF) Version 1.1 compliant Provided (1) Consecutive numbering (2) Auto reset (3) Manual reset 2 Standard Parameters plus up to three custom processing parameters can be set.	<b>SOFTWARE</b>	Browsing & Printing Other Drivers Image Manipulation	Windows 98 (including SE)/2000/Me/XP OS 9.0 - 9.2, OS X v10.1/v10.2
<b>COLOUR MATRIX</b>	Type	Two types of colour space, sRGB and Adobe RGB.	<b>DIRECT PRINT</b>	Canon Printers	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, RAW & JPEG simultaneous recording, Digital Print Order Format (DPOF) Version 1.1 compliant Provided (1) Consecutive numbering (2) Auto reset (3) Manual reset 2 Standard Parameters plus up to three custom processing parameters can be set.	<b>SOFTWARE</b>	Browsing & Printing Other Drivers Image Manipulation	Windows 98 (including SE)/2000/Me/XP OS 9.0 - 9.2, OS X v10.1/v10.2
<b>VIEWFINDER</b>	Viewfinder Coverage (Vertical/Horizontal) Magnification Eyepoint Dioptr Correction	Pentamirror 95% 0.88x 21mm -3 to +1 dpt	<b>PictBridge</b>	PictBridge	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, RAW & JPEG simultaneous recording, Digital Print Order Format (DPOF) Version 1.1 compliant Provided (1) Consecutive numbering (2) Auto reset (3) Manual reset 2 Standard Parameters plus up to three custom processing parameters can be set.	<b>SOFTWARE</b>	Browsing & Printing Other Drivers Image Manipulation	Windows 98 (including SE)/2000/Me/XP OS 9.0 - 9.2, OS X v10.1/v10.2
			<b>OTHER FEATURES</b>	LCD Panel (EL) Illumination Intelligent Orientation Sensor Histogram	JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, RAW & JPEG simultaneous recording, Digital Print Order Format (DPOF) Version 1.1 compliant Provided (1) Consecutive numbering (2) Auto reset (3) Manual reset 2 Standard Parameters plus up to three custom processing parameters can be set.	<b>SOFTWARE</b>	Browsing & Printing Other Drivers Image Manipulation	Windows 98 (including SE)/2000/Me/XP OS 9.0 - 9.2, OS X v10.1/v10.2
					JPEG (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, RAW & JPEG simultaneous recording, Digital Print Order Format (DPOF) Version 1.1 compliant Provided (1) Consecutive numbering (2) Auto reset (3) Manual reset 2 Standard Parameters plus up to three custom processing parameters can be set.	<b>SOFTWARE</b>	Browsing & Printing Other Drivers Image Manipulation	Windows 98 (including SE)/2000/Me/XP OS 9.0 - 9.2, OS X v10.1/v10.2

\*In display formats 1 & 2 any over exposed highlight areas will blink in the image display.

Some images are simulated for clarity of reproduction.

The specifications above are based on Canon's testing standards.

The camera's specifications and physical appearance are subject to change without notice.™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.



you can  
**Canon**



**Canon Inc**  
30-2 Shimomaruko  
3-Chome, Ohta-ku  
Tokyo 146-8501  
Japan

**Canon Europa NV**  
Bovenkerkerweg 59-61  
1185 XB Amstelveen  
The Netherlands

[www.canon-europe.com](http://www.canon-europe.com)

0039W436 © Canon Europa N.V. 2003